



Product Technical Bulletin

37-511

Product Type	EVA hot melt adhesive										
Suggested Use(s)	Product assembly										
Typical Properties	<table><tr><td>Operating Temp.</td><td>325-360F</td></tr><tr><td>Viscosity</td><td>1500-2500 cps @ 350F</td></tr><tr><td>Softening Point</td><td>160F</td></tr><tr><td>Set Speed</td><td>Slow</td></tr><tr><td>Appearance</td><td>Opaque pellet</td></tr></table>	Operating Temp.	325-360F	Viscosity	1500-2500 cps @ 350F	Softening Point	160F	Set Speed	Slow	Appearance	Opaque pellet
Operating Temp.	325-360F										
Viscosity	1500-2500 cps @ 350F										
Softening Point	160F										
Set Speed	Slow										
Appearance	Opaque pellet										
Shelf Life	2 years from date of sale										
Characteristics	Slow set with aggressive and long open time. Recommended for plastic to plastic applications. Complies with FDA 21CFR175.105 for indirect Food contact applications.										
Storage and Handling	Do not mix with other adhesives. Keep containers covered to prevent contamination. Store in a cool, dry location. Purge system with paraffin wax for changeovers.										

The information contained herein is based on tests and reports considered to be reliable but is presented without guarantee or responsibility as to the applicability of correctness of this information or the suitability of our products whether used singly or in combination with other products. The product referred to above is sold without warranty, express or implied.
