

Product code

CM-4/50F

Product group

Polyamide Folder-Gluer Belts

Joining method

Flexproof

Contact

Laurent Chouvet

Edition date

08/05/2024

Status

Master

Important


- Joining is also possible with other Habasit devices.
- Machine setting data should be derived from the relevant operating instructions.
- Read the operating instructions of the necessary tools carefully before making the first joint.
- All data are approximate values and defined under the following standard climatic conditions:
 - 23 °C/73 °F, 50% relative humidity (DIN 50005/ISO 554), working voltage 225-235 V / 105-115 V.
 - Any change of these data may require different temperature and/or time and/or pressure.
- For further support, please contact the Habasit company responsible for your location.

Finger cutting

Finger cutting device	AF-1200/1201 family
-----------------------	---------------------

Dimensions

Trim finger tips to assure optimal joining quality.



	mm	in.
A	10	0.39
B	80	3.15









Hot pressing

Hot pressing device	PM-02/04/06 family, PM-09/160W family
---------------------	---------------------------------------

Parameters

Pressing temperature, top	170 °C 338 °F
Pressing temperature, bottom	170 °C 338 °F
Pressure setting	1.2 bar 17 psi
Pressing time	5 min

Inserts

Top		
8		Heating plate; top
7		Heat equalizing plate; top
6		Teflon
5		Belt (conveying side up)
4		Teflon
3		Molleton
2		Heat equalizing plate; bottom
1		Heating plate; bottom
Bottom		

Product liability

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.