




AutoSeal® FD 2096

PRODUCTION PRESSURE SEALER



www.update ltd.com

1-800-229-0009



- Bottom-suction air feed system
- Processes up to 30,000 forms per hour
- Handles forms up to 17" long
- Heavy duty construction
- Adjustable 17" ball transport deck

FORMAX®


www.formax.com

Local Dealer:

The **AutoSeal® FD 2096** uses patented pressure seal technology to efficiently process cut-sheet forms at speeds of **up to 30,000 forms per hour**. Its **bottom-suction air-feed system** provides accurate feeding and allows for **continual loading** of forms, dramatically reducing down time. Set-up is quick and easy with **rugged metal fold pates**, clearly marked with standard and metric markings. The sealing unit utilizes an **adjustable 17" 8-ball transport deck** for a smooth, transition from the fold rollers into the sealer. Features include **user-friendly operator controls**, **sound-dampening fold plate** covers for quieter operation, **rugged locking casters**, and a **high-capacity 24" output conveyor** which is collapsible for convenient storage.




User-Friendly Controls
On/Off switch and simple speed control knob




Rotating Air-Suction Drum
Reliably separates sheets for accurate feeding



Resettable Counter
6-digit resettable LED counter to keep track of processed forms



24" Outfeed Conveyor
Integrated conveyor is collapsible for convenient storage



Sound-Reducing Insulation
Fold plates are covered and insulated to reduce noise

STANDARD FEATURES

Top-loading bottom air feed
Variable speed control
Heavy duty fold rollers
Adjustable 17" 8-ball transport deck
Rugged fold plates
Precision ground clutching 4-roller system
Fully-enclosed air-feed pump
Rotating air suction drum
Casters for easy transport
7-point quick-release fold stops
24" integrated outfeed conveyor
Adjustable stacker wheels
User-friendly adjustments
Resettable 6-digit LED counter
Insulated fold plates for noise reduction
Infrared fault detection
Plexi-cover with safety interlock
Static eliminator brush

OPTIONS

402 Series Jogger: Reduces static electricity and aligns forms for proper feeding
V-Stack36i Stacker: Vertically stacks up to 22" of folded documents, making them easier to unload
Center Slitter: For applications including 2-up postcards

SPECIFICATIONS

| | |
|--------------------------------|--|
| Hopper Capacity | Up to 350 sheets 24# |
| Speed | Up to 30,000 forms per hour |
| Usage | Mid-Volume Production |
| Form Size | Up to 12" W, up to 17" L (305mm, 432mm) |
| Dimensions (Conveyor Extended) | 86" L x 28" W x 42" H (219 x 71 x 107cm) |
| Dimensions (Conveyor Closed) | 64" L x 28" W x 42" H (163 x 71 x 107cm) |
| Weight | 450 lbs (204kg) |
| Power | 120V 60Hz, 30Amp, single phase |
| Power Plug | NEMA L5-30P |