

**GR-PQ-59 Guiderail**

Guide rail of fixed width inclusive a covering plate and 2 metal clamps.



| Technical data |          |
|----------------|----------|
| Custom Tariff  | 85159080 |

| Available versions | Item number |
|--------------------|-------------|
| GR-PQ-59-M-006     | H080672006  |
| GR-PQ-59-M-008     | H080672008  |
| GR-PQ-59-M-010     | H080672010  |
| GR-PQ-59-M-011     | H080672011  |
| GR-PQ-59-M-012     | H080672012  |
| GR-PQ-59-M-013     | H080672013  |
| GR-PQ-59-M-014     | H080672014  |
| GR-PQ-59-M-015     | H080672015  |
| GR-PQ-59-M-016     | H080672016  |
| GR-PQ-59-M-018     | H080672018  |
| GR-PQ-59-M-020     | H080672020  |
| GR-PQ-59-M-022     | H080672022  |
| GR-PQ-59-M-025     | H080672025  |
| GR-PQ-59-M-030     | H080672030  |
| GR-PQ-59-M-035     | H080672035  |
| GR-PQ-59-M-040     | H080672040  |
| GR-PQ-59-M-050     | H080672050  |
| GR-PQ-59-I-3/8     | H080672113  |
| GR-PQ-59-I-1/2     | H080672101  |
| GR-PQ-59-I-5/8     | H080672114  |
| GR-PQ-59-I-3/4     | H080672102  |
| GR-PQ-59-I-7/8     | H080672109  |
| GR-PQ-59-I-1       | H080672103  |
| GR-PQ-59-I-1_1/8   | H080672110  |
| GR-PQ-59-I-1_1/4   | H080672104  |
| GR-PQ-59-I-1_3/8   | H080672105  |
| GR-PQ-59-I-1_1/2   | H080672106  |
| GR-PQ-59-I-1_5/8   | H080672111  |
| GR-PQ-59-I-1_3/4   | H080672107  |
| GR-PQ-59-I-1_7/8   | H080672112  |
| GR-PQ-59-I-2       | H080672108  |
| GR-PUR 12/5        | H088000606  |
| GR-PUR 25/5        | H088000605  |
| GR-PUR 28/5        | H088000604  |

| Available versions | Length                | Width                  | Height                | Weight              | Belt Width |
|--------------------|-----------------------|------------------------|-----------------------|---------------------|------------|
| GR-PQ-59-M-006     | 120 mm ( 4.724 inch ) | 25.0 mm ( 0.984 inch ) | 8.3 mm ( 0.327 inch ) | 0.130 kg ( 0.3 lb ) |            |
| GR-PQ-59-M-008     | 120 mm ( 4.724 inch ) | 25.0 mm ( 0.984 inch ) | 8.3 mm ( 0.327 inch ) | 0.140 kg ( 0.3 lb ) |            |
| GR-PQ-59-M-010     | 120 mm ( 4.724 inch ) | 35.0 mm ( 1.378 inch ) | 8.3 mm ( 0.327 inch ) | 0.140 kg ( 0.3 lb ) |            |
| GR-PQ-59-M-011     | 120 mm ( 4.724 inch ) | 35.0 mm ( 1.378 inch ) | 8.3 mm ( 0.327 inch ) | 0.140 kg ( 0.3 lb ) |            |
| GR-PQ-59-M-012     | 120 mm ( 4.724 inch ) | 35.0 mm ( 1.378 inch ) | 8.3 mm ( 0.327 inch ) | 0.140 kg ( 0.3 lb ) |            |
| GR-PQ-59-M-013     | 120 mm ( 4.724 inch ) | 35.0 mm ( 1.378 inch ) | 8.3 mm ( 0.327 inch ) | 0.140 kg ( 0.3 lb ) |            |
| GR-PQ-59-M-014     | 120 mm ( 4.724 inch ) | 35.0 mm ( 1.378 inch ) | 8.3 mm ( 0.327 inch ) | 0.150 kg ( 0.3 lb ) |            |
| GR-PQ-59-M-015     | 120 mm ( 4.724 inch ) | 35.0 mm ( 1.378 inch ) | 8.3 mm ( 0.327 inch ) | 0.160 kg ( 0.4 lb ) |            |
| GR-PQ-59-M-016     | 120 mm ( 4.724 inch ) | 35.0 mm ( 1.378 inch ) | 8.3 mm ( 0.327 inch ) | 0.160 kg ( 0.4 lb ) |            |

|                  | <i>inch )</i>                   | <i>)</i>                          | <i>)</i>                         | <i>)</i>                      |
|------------------|---------------------------------|-----------------------------------|----------------------------------|-------------------------------|
| GR-PQ-59-M-018   | 120 mm ( 4.724<br><i>inch )</i> | 35.0 mm ( 1.378<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-M-020   | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-M-022   | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-M-025   | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-M-030   | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-M-035   | 120 mm ( 4.724<br><i>inch )</i> | 70.0 mm ( 2.756<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-M-040   | 120 mm ( 4.724<br><i>inch )</i> | 70.0 mm ( 2.756<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.200 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-M-050   | 120 mm ( 4.724<br><i>inch )</i> | 70.0 mm ( 2.756<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.210 kg ( 0.5<br><i>lb )</i> |
| GR-PQ-59-I-3/8   | 120 mm ( 4.724<br><i>inch )</i> | 35.0 mm ( 1.378<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.140 kg ( 0.3<br><i>lb )</i> |
| GR-PQ-59-I-1/2   | 120 mm ( 4.724<br><i>inch )</i> | 35.0 mm ( 1.378<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.140 kg ( 0.3<br><i>lb )</i> |
| GR-PQ-59-I-5/8   | 120 mm ( 4.724<br><i>inch )</i> | 35.0 mm ( 1.378<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.140 kg ( 0.3<br><i>lb )</i> |
| GR-PQ-59-I-3/4   | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-7/8   | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-1     | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-1_1/8 | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.160 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-1_1/4 | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-1_3/8 | 120 mm ( 4.724<br><i>inch )</i> | 70.0 mm ( 2.756<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.200 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-1_1/2 | 120 mm ( 4.724<br><i>inch )</i> | 50.0 mm ( 1.969<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.170 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-1_5/8 | 120 mm ( 4.724<br><i>inch )</i> | 70.0 mm ( 2.756<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.200 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-1_3/4 | 120 mm ( 4.724<br><i>inch )</i> | 70.0 mm ( 2.756<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.200 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-1_7/8 | 120 mm ( 4.724<br><i>inch )</i> | 70.0 mm ( 2.756<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.200 kg ( 0.4<br><i>lb )</i> |
| GR-PQ-59-I-2     | 120 mm ( 4.724<br><i>inch )</i> | 70.0 mm ( 2.756<br><i>inch )</i>  | 8.3 mm ( 0.327<br><i>inch )</i>  | 0.200 kg ( 0.4<br><i>lb )</i> |
| GR-PUR 12/5      | 250 mm ( 9.843<br><i>inch )</i> | 128.0 mm ( 5.039<br><i>inch )</i> | 39.9 mm ( 1.571<br><i>inch )</i> | kg ( <i>lb</i> )              |
| GR-PUR 25/5      | 250 mm ( 9.843<br><i>inch )</i> | 128.0 mm ( 5.039<br><i>inch )</i> | 39.9 mm ( 1.571<br><i>inch )</i> | kg ( <i>lb</i> )              |
| GR-PUR 28/5      | 250 mm ( 9.843<br><i>inch )</i> | 128.0 mm ( 5.039<br><i>inch )</i> | 39.9 mm ( 1.571<br><i>inch )</i> | kg ( <i>lb</i> )              |

### Disclaimer

#### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.