



## ONYX HD6500

The HD6500 is a 14 inch (356 mm) open-ended punch that features the 2-bolt EZ Change Slide out die system for changing punch patterns in 60 seconds. The HD6500 was designed with the operator in mind, offering quick, easy set-up including easy pin pulls and pre-set paper stop positions. With a three year limited warranty, this is truly the industry standard.

Rated up to 40 sheets or up to 80 pages of 20 pound (80 gsm) bond paper. The number of sheets depends on the paper weight and punch pattern used. Designed for mid to high volume commercial and corporate use.

UL & CE Approved



More than **98%** recyclable



YOUR UNLIMITED PARTS SOURCE  
FOR PRINT FINISHING AND PACKAGING

1.800.229.0009 | [www.updateltd.com](http://www.updateltd.com)

## PRODUCT FEATURES

- Patented Auto Reverse Feature. Our Overload Detection Feature triggers an auto-reversing function to reduce jamming in the punch.
- 2-Bolt EZ Change Die System.
- The HD6500 Has More Than 20 Interchangeable Dies Available. 12 Hole Patterns are standard. (Each die is priced separately).
  - Combs
  - Wire Loop
  - Plastic Coils
  - Velo Bind™ GBC
  - 3 Hole Loose Leaf
- 25 Cycles Per Minute.
- Pre-set Paper Stop Guide for easy setup.
- 14 inch (356 mm) Open Ended Punching, Allows for Wider Applications.
- All Punch Pins easily disengaged.
- Easy, "Paper to Pin," sight alignment, for balanced hole to edge margins on odd-sized applications.
- Standard Foot Pedal, optional Versa Switch, or Palm Switch.
- 3 Year Warranty.
- Smooth, Quiet, Power on Demand Operations.
- Large EZ View Chip Tray.
- All Metal Fabrication.

## MACHINE SPECIFICATIONS

Electrical Requirements			Weight		Assembled Dimensions		
Volts AC	AMPS	Hz	Machine	Shipping	Height	Width	Depth
115	4	60	70 lbs.	81 lbs.	9"	17"	20"
230	2	50	32 Kg	37 Kg	229 mm	432 mm	508 mm

Dies available for Coil,  
Wire, & Comb

