

### Main industry segments



Postal/mail sorting

### Applications

Feeder belt, Folder belt, Letter transport belt, Machine tape, Mail handling / mail sorting belt, Paper handling belt, Sheeter/Crosscutter belt

### Special features

Abrasion resistant on both sides, Constant and gentle positive grip, Dimensionally stable, Elastic



Product Construction / Design	
Conveying side surface	Fine structure
Conveying side property	Adhesive
Conveying side color	Green
Traction layer (material)	Hamid
Number of Fabrics	0
Pulley side surface	Rough structure
Pulley side property	Adhesive
Pulley side color	Black

Product characteristics	
Antistatically equipped	Yes
Adhesive free joining method	Yes

Technical data		
Thickness of belt	1.45 mm	0.06 inch
Mass of belt (belt weight)	1.4 kg/m <sup>2</sup>	0.287 lb/sqft
Tensile force for 8% elongation (k8% static) per unit of width (Habasit Standard SOP3-155 / EN ISO 21181):	2.6 N/mm	15 lbf/in
Tensile force for 8% elongation after relaxation (k8% relaxed) per unit of width (Habasit Standard SOP3-155 / EN ISO 21181):	1.8 N/mm	10 lbf/in
Min. operating temperature admissible (continuous)	-20 °C	-4 °F
Max. operating temperature admissible (continuous)	60 °C	140 °F
Seamless manufacturing width	1200 mm	47 inch

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

### Joining related properties

Link to JDS:

<http://pdchmp04.habasit.com/HNET/fabren.nsf/vwGetJDS?OpenView&productCode=MAM-04H>

Joining method	Unit	Quickmelt	Flexproof 8 x 30
Pulley diameter (minimum)	mm <i>inch</i>	15 <i>0.59</i>	
Pulley diameter minimum with counter flection	mm <i>inch</i>	15 <i>0.59</i>	
Slider bed suitable		Yes	
Carrying rollers suitable		Yes	
Troughed installation suitable		Yes	

### Chemical resistance

Link to 'Chemical resistance information': <http://www.habasit.com/en/chemical-resistance.htm>

### Mode of use or conveyance

Declined, Horizontal, Inclined, Twists with short center distance, Vertical

### Calculations

For most applications calculation is not required. Should you still need a calculation: please ask Habasit.

### Recommendation

Elastic belt: Initial elongation depends on belt load and application, Initial elongation between 3 to 8% is recommended

For details consult 'Storage and handling requirements for belts and machine tapes' or contact Habasit, Protect belts from sunlight/UV-radiation/dust and dirt. Store spare belts in a cool and dry place and if possible in their original packaging.

Group	Hamid Machine Tapes
Sub-Group	-
Item number	H010100207
Customs tariff number	40101200

### Disclaimer

#### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.