

Hyperion 924IPsv2 Short-Range Pulsed DC Ionising Bar



Product Code: 924IPsv2

Powered by 24V DC the Hyperion 924IPsv2 is the most compact pulsed DC bar available on the market.

The 924IPsv2 features Meech's Ion Current Monitoring (ICM) technology, this ensures performance is maintained with local and remote alerts when the bar needs cleaning.

Fully BarMaster and SmartControl compatible, the output voltage, frequency and balance can be adjusted. These features will help optimise the 924IPsv2 for specific applications.

Product Data Sheet

Published Date: 20.02.2024



Features & Benefits

Optimum Working Distance	20-150mm; suitable for short range applications, such as web paths on converting machinery, printing presses or applications that have traditionally used AC equipment.
Compact Size & Full Length Ionisation	At just 22.1mm (W) x 31.2mm (H), it will fit into tight installations. The bar is also designed to give full performance over its entire length.
Low Voltage Wiring	Requiring a 24V DC supply removes the need for high voltage wiring to the ionising bar.
Integrated Power Supply (IPS)	The integral pulsed DC power supply uses surface-mount high voltage components. This reduces the overall size of the bar, making it the most compact 24V DC bar available.
Adjustable Output	Output voltage, frequency and balance can be adjusted using the BarMaster programmer. Adjustable output optimises the bar for sensitive applications like RFID.
Adjustable Clean Pin Alert	Meech Ion Current Monitoring (ICM) technology detects when the 924IPsv2 needs to be cleaned. The LED on the bar alerts operators of the need for cleaning. This ensures peak performance is maintained.
Environmental Protection	IP66 construction makes the bar suitable for harsh environments.
Dual Alarm Lines - Clean Pin Alert & Fault Output	An output signal will activate when the bar needs cleaning or a fault has been detected. The flexible configuration of the alarm lines allow them to be interfaced with PLC's, buzzers and remote lamps. This will alert operators remotely to check the bar.

Product Data Sheet

Published Date: 20.02.2024



Technical Characteristics

Dimensions (W x H)	22.1mm x 31.2mm
Maximum Length	3960mm
Weight	0.5kg/metre
Construction	FR ABS
Mounting	'T' Slot with M4 x 20mm studs
Emitters	Sharp titanium pins
Input Voltage and Current	24V DC (21-27V DC) Max 500mA
Output Voltage	Adjustable, up to +/- 7kV pulsed DC
Electrical Connection	4 Pole M8
Output Frequency	Default: 20Hz (Adjustable with BarMaster)
Output Balance	Default: 54% Positive, 46% Negative (Adjustable with BarMaster)
Environmental Protection	IP66
Max Ambient Temperature	60°C
Certifications	CE, UL.

Product Data Sheet

Published Date: 20.02.2024



Standard Sizes

Standard Size	No. of T slides
0240	2
0280	2
0320	2
0360	2
0400	2
0440	2
0480	2
0520	2
0560	2
0600	2
0680	2
0760	2
0840	2
0920	2
1000	3
1080	3
1160	3
1240	3
1320	3
1400	3
1560	4
1720	4
1880	4
2040	5
2200	5
2360	5
2520	6
2680	6
2840	6
3000	6
3160	7
3320	7
3480	7
3640	8
3800	8

Dimensions: 22,1, 31,2, 3, Standard Length, LED indicator, Murr Power Connection, M4 Mounting T-Slides

Meech
Meech International
2 Meech Point
Ridge Road, Wilsey
CO28 0PL, UK
Tel: +44 (0) 1893 706700
Fax: +44 (0) 1893 778877
email: s.d.4@meech.com
web: www.meech.com

COPYRIGHT © MEECH & THE ELIMINATORS
THIS DOCUMENT AND THE INFORMATION
HEREIN IS THE PROPERTY OF THE MEECH
GROUP AND SHOULD NOT BE COPIED IN WHOLE
OR PART OR USED FOR REPRODUCTION OR
OTHERWISE DISCLOSED WITHOUT THE PRIOR
WRITTEN CONSENT OF MEECH INTERNATIONAL

TITLE: 924 Bar
DRAWING No.: A924IPS-
MATERIAL: Various
FINISH: Various

TOLERANCE: Machined Work: 0.05mm, Unmachined Fabrications: 0.1mm, Angular: 0.2°
DIMENSIONS: MM, DO NOT SCALE

PROJECTION: Sheet A4, Scale 1:1

Date: 18/05/2015, **Drawn by:** David Hyde
REVISION: 1
SHEET: 1 / 1
STATUS: Production

Add standard size to drawing number to get the product code. e.g. 240mm bar would be A924IPS-0240