Fabrication Tools PT-55





Description

The PT-55 is a hot-pressing device designed for the joining of Habasit machine and spindle tape up to 50 mm wide and 2.5 mm thick by way of the Thermofix procedure. The maximum possible skiving length is 35 mm. With guide rails in the width appropriate to the application and the possibility of connecting the hot press to between 110 and 230 V, the PT-55 offers an extremely flexible joining system.

Technical data						
Joining System	Ther	mofix				
Belt/tape width max.	50	mm	2	inch		
Belt/tape width max. For joining angle of 75°	45	mm	2	inch		
Belt/Tape thickness max.	3	mm	0.10	inch		
Dimensions (LxWxH)	280 x 63 x 95	mm	11.00 x 2.50 x 3.70	inch		
Max. skiving length	35	mm	1.4	inch		
Cooling media	Ambient air					
Adjustable Temperature	Fixed					
Working temperature	120	°C	248	°F		
Weight net	0.72	kg	1.60	lb		

Available versions	ltem number	Power supply	Power
PT-55/6	H080691400	1ph 120V 60Hz	150W
PT-55/8	H080691420	1ph 230V 50Hz	150W

Group GFT Tools

Sub-Group Hot pressing devices

Customs tariff number 85158090

Fabrication Tools PT-55



Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.