

R42915

Suggested Use(s)	Cartons, uncoated paper, aqueous coated paper, some wax coated paper.
Equipment Application	Contact extrusion, bottom pot, laminating
Typical Properties	
Viscosity	1200-1700 cps
Wt Solids (%)	52-56
pH	4.0-6.0
Bulk Density	8.7-9.1 lbs/gal
Appearance	white, colored or UV fluorescing liquid
Shelf Life	6 months from date of sale
Characteristics	Specially formulated for gluing aqueous coatings to paper stock. Formulated for increased penetration on difficult to bond paper stock. Provides good machining characteristics with fast set and moderate open time. Meets compositional requirements of 21CFR175.105 for adhesives intended for incidental food contact applications.
Storage and Handling	Agitate thoroughly before use. Do not store directly on concrete floor. Storage temperature 60-90F Keep containers covered to prevent skinning and contamination. Protect from freezing. Clean dried film with water/acetone mixture. Clean wet film with warm water. Do not mix with other adhesives.

The information contained herein is based on tests and reports considered to be reliable but is presented without guarantee or responsibility as to the applicability of correctness of this information or the suitability of our products whether used singly or in combination with other products. The product referred to above is sold without warranty, express or implied.

TBR42915 – rev 2 – 7.16.2009